

FOCUS MIG 400 s-w CONFIGURATION

Fixed configuration 79541790:

- 4 m MV 450 MIG-A Twist (1.2)
- 3 m earth cable - clamp
- Trolley with wheels for cylinder
- Built-in cooling unit
- Supplied in cardboard packaging
- Instruction manual
- Quickguide
- Red CEE 32 A mains plug



MIGATRONIC

FOCUS MIG 400 s-w USP

USP

- Ease of operation
- High duty cycle
- Separate wire feed unit
- MIG-A Twist
- 4-roll wire feed system
- Water cooling
- Ready to weld

Value

Classic panel with stepless functions and control á la step-regulated MIG equipment

High performance – no delay caused by cooling

MWF 27 with sep. plug connections for large working range

Ergo-torch with turnable swan neck

Safe feeding also of the soft wires

Long life of parts and handle

Supplied ready to weld with trolley and mains plug

FOCUS MIG 400 s-w DATA

Data:

Current range	10 - 400 A		
Mains fuse	20 A slow (3F)		
Duty cycle	40°	100 %	300 A
	40°	60 %	365 A
	20°	100 %	335 A
	20°	60 %	400 A
Dimension H x W x L	1340 x 500 x 940		
Protection class	IP 23		
Weight	79 kg		